



New with
**refrigerant
R290a**



Vulcano

The World's First multifunctional food showcase

Vulcano enables you to present your food in its ideal ambience conditions: hot and dry, hot and humid, refrigerated or neutral. With its ultra-short changing cycles of only 30 minutes, the showcase adapts to your varying selection of dishes in an optimum and flexible manner, thus making perfect use of space and offering maximum flexibility in its usage.

The large seamless presentation area offers greatest versatility in the use of dishes and accessories of various shapes and sizes. This unique showcase combines induction heating with an active, variable fresh steam system and state of the art circulating-air refrigeration, thus guaranteeing enduring freshness of your dishes. The LED lighting (2 shades of white) provides perfect illumination.

Vulcano enables you to quickly adapt your selection to the changing demands of your customers on a 24/7 basis.

Your advantages

- ❑ Maximum variability with slight space requirements
- ❑ Short switching and changing intervals for four different ambience conditions: hot and dry, hot and humid, refrigerated or neutral
- ❑ Enduring, continuous freshness of the dishes on account of the variable fresh steam system
- ❑ Heat generation by large-area induction
- ❑ Chilled products stay fresh longer due to active circulating-air refrigeration (class 2 cooling energy)
- ❑ State of the art energy-efficient technology
- ❑ Attractive food presentation due to LED and infra-red lighting
- ❑ Fast switching between attended and self-service by simply inserting the front glass
- ❑ Available in build-in, free standing and mobile versions
- ❑ Versions with self-cooling or connection to central cooling
- ❑ Comprehensive range of flexible accessories



Set the ambience conditions to suit your needs



Warm food presentation



Neutral food presentation



Refrigerated food presentation

Technical specifications

| Model | Dimensions (W x D x H) | Presentation surface (W x D x H) | Voltage | Electrical power with fresh steam | Electrical power without fresh steam | Max. nominal current | Plug |
|-----------|------------------------|----------------------------------|---------|-----------------------------------|--------------------------------------|----------------------|---------|
| Vulcano 2 | 780 x 900 x 1300 mm | 650 x 600 mm | 400 V | 3800 W | 2250 W | 7.0 A | CEE 16A |
| Vulcano 3 | 1120 x 900 x 1300 mm | 975 x 600 mm | 400 V | 4900 W | 3350 W | 10.5 A | CEE 16A |
| Vulcano 4 | 1460 x 900 x 1300 mm | 1300 x 600 mm | 400 V | 6000 W | 4450 W | 14.0 A | CEE 16A |

Please contact your sales representative for further versions and configuration options.